Description:

The purpose of the section is to highlight the current applicable UMD Design Standards for basic design and installation of plumbing fixtures and equipment.

Related Sections:

• 10 21 00 Restroom Requirements

Effective Date:

January 1, 2023

Applicable Standards:

• WSSC – Washington Suburban Sanitary Commission

General Requirements:

The provisions of WSSC apply, as well as industry standard good design practice for educational institutions. The design must reflect the University's need to perform maintenance and repair without interruption to educational activity. The University encourages the Plumbing consultant to employ water saving and energy-efficient design, consistent with goals of LEED and the project budget.

Specific Requirements:

Products:

Piping:

- See the Piping / Valves section.
- See the Mechanical Design Standards section for the required color code.

Valves

- See the Piping / Valves section.
- Gate and plug valves shall not be used without approval from the Plumbing Shop.

Fixtures

Furnish fixtures and appurtenances in accordance with the following schedule.

Fixture	Material	Manufacturers	Notes
Water Closet	Flush valve, wall hung with heavy-	American Standard,	Valve by Sloan, American
	duty carrier, white vitreous china	Toto, and Kohler	Standard, Toto, Zurn and
	elongated bowl and open toilet seat.		Delany
	Tank type will not be permitted.		
Urinal	Wall hung vitreous china, without	American Standard,	Valve by Sloan, American
	strainers.	Toto, and Kohler	Standard, Toto, Zurn and
			Delany
Lavatory	Wall hung or oval self-rimming where	American Standard	Faucet by American
	installed in countertops. Vitreous	and Kohler	Standard, Kohler and
	china material.		Chicago Faucet
Sink	Stainless steel, self-rimming.	Elkay and Just	Faucet by American
	Compartment quantity and size as		Standard, Kohler and
	required for function.		Chicago Faucet
Mop Sink	Wall mounted, cast iron, self-	American Standard	Faucet by American
	supporting P-trap with clean out.	and Kohler	Standard and Kohler
Electric Water	Wall mounted, ADA compliant with	Oasis, Elkay and	
Cooler	hand- operated (valve-type)	Halsey Taylor	
	bubblers.		

Plumbing 22.00.00

Emergency Wash	Eye	Squeeze handle operation and ABS plastic eye/face wash head. Thermostatic mixing valve with builtin shutoff in the event of hot or cold	Gardian and Haws	
		water supply failure.		

Design Guidelines:

- Provide a back-up pump for all domestic hot water re-circulating systems.
- Provide a separate re-circulating pump for each domestic hot water system that has a different temperature setpoint.
- Provide a valved by-pass on pressure reducing valve assemblies.
- Waterless urinals are not allowed.